

# DURASPANDREL

Roofing using seam lock system. Guaranteed no drilling and screws.

## PRODUCT INFO

<b>SUBSTRATES</b>	Hot-dip Metallic Coated Steel - Hot-dip Zinc-Coated Steel - Hot-dip 55% Aluminum-Zinc Alloy Coated Steel
<b>NOMINAL THICKNESS</b>	0.30 mm to 0.40 mm
<b>FEED WIDTH</b>	152 mm and 229 mm
<b>EFFECTIVE COVERAGE</b>	111 mm and 187 mm (+/- 2mm)

**PAINT COATING SYSTEM** Oven baked Oil free Polyester topcoat over a corrosion-resistant Primer with Oil free Polyester backing coat  
PVDP, SMP, available upon request

**PAINT COATING THICKNESS / AVAILABLE COLORS** Regular Colors: Beige and White  
Topcoat : 12 – 15 microns  
Backing Coat : 4–8 microns


Woodgrain: Oakwood and Mocha  
Topcoat : 20 – 25 microns  
Backcoat : 5 – 7 microns

\*\* Available with perforations. \*\*

### PRODUCT SPECIFICATIONS



Plain (111)



Plain (187)



Mini Swage (111)



Mini Swage (187)





Multi Rib (111)



Multi-Rib (187)



Mini Corr (111)



Mini-Corr (187)

**DURASPANDEL 9" WIDE PROFILE**  
**(111MM) (+/- 2mm)**

**DURASPANDEL 9" WIDE PROFILE**  
**(187MM) (+/- 2mm)**

### PERFORATION DESIGN (111mm)

#### DESIGN 1



#### DESIGN 2



## HANDLING, STORAGE AND INSTALLATION GUIDELINES

